

湿度\露点\PPM对照表

露点摄氏度℃	露点华摄氏度F	水蒸气压力	PPM水份的体积比	相对湿度	PPM水份的质量比
-150	-238	7*10-15	9.2*10-12	—	5.7*10-12
-140	-220	3*10-10	4.0*10-7	—	2.5*10-7
-130	-202	7*10-8	9.2*10-5	—	5.7*10-5
-120	-184	10*10-8	1.3*10-4	5.4*10-7	8.1*10-5
-118	-180	0.00000016	0.00021	0.0000009	0.00013
-116	-177	0.00000026	0.00034	0.0000014	0.00021
-114	-173	0.00000043	0.00057	0.0000023	0.00035
-112	-170	0.00000069	0.00091	0.0000037	0.00057
-110	-166	0.0000010	0.00132	0.0000053	0.00082
-108	-162	0.0000018	0.00237	0.0000096	0.0015
-106	-159	0.0000028	0.00368	0.000015	0.0023
-104	-155	0.0000043	0.00566	0.000023	0.0035
-102	-152	0.0000065	0.00855	0.000035	0.0053
-100	-148	0.0000099	0.0130	0.000053	0.0081
-98	-144	0.000015	0.0197	0.000080	0.012
-96	-141	0.000022	0.0289	0.00012	0.018
-94	-137	0.000033	0.0434	0.00018	0.027
-92	-134	0.000048	0.0632	0.00026	0.039
-90	-130	0.000070	0.0921	0.00037	0.057
-88	-126	0.00010	0.132	0.00054	0.082
-86	-123	0.00014	0.184	0.00075	0.11
-84	-119	0.00020	0.263	0.00107	0.16
-82	-116	0.00029	0.382	0.00155	0.24
-80	-112	0.00040	0.526	0.00214	0.33
-78	-108	0.00056	0.737	0.00300	0.46
-76	-105	0.00077	1.01	0.00410	0.63
-74	-101	0.00105	1.38	0.00559	0.86

-72	-98	0.00143	1.88	0.00762	1.17
-70	-94	0.00194	2.55	0.0104	1.58
-68	-90	0.00261	3.43	0.0140	2.13
-66	-87	0.00349	4.59	0.0187	2.84
-64	-83	0.00464	6.11	0.0248	3.79
-62	-80	0.00614	8.08	0.0328	5.01
-60	-76	0.00808	10.6	0.0430	6.59
-58	-72	0.0106	13.9	0.0565	8.63
-56	-69	0.0138	18.2	0.0735	11.3
-54	-65	0.0178	23.4	0.0948	14.5
-52	-62	0.0230	30.3	0.123	18.8
-50	-58	0.0295	38.8	0.157	24.1
-48	-54	0.0378	49.7	0.202	30.9
-46	-51	0.0481	63.3	0.257	39.3
-44	-47	0.0609	80.0	0.325	49.7
-42	-44	0.0768	101	0.410	62.7
-40	-40	0.0966	127	0.516	78.9
-38	-36	0.1209	159	0.644	98.6
-36	-33	0.1507	198	0.804	122.9
-34	-29	0.1873	246	1.00	152
-32	-26	0.2318	305	1.24	189
-30	-22	0.2859	376	1.52	234
-28	-18	0.351	462	1.88	287
-26	-15	0.430	566	2.30	351
-24	-11	0.526	692	2.81	430
-22	-8	0.640	842	3.41	523
-20	-4	0.776	1020	4.13	633
-18	0	0.939	1240	5.00	770
-16	3	1.132	1490	6.03	925
-14	7	1.361	1790	7.25	1110

-12	10	1.632	2150	8.69	1335
-10	14	1.950	2570	10.4	1596
-8	18	2.326	3060	12.4	1900
-6	21	2.765	3640	14.7	2260
-4	25	3.280	4320	17.5	2680
-2	28	3.880	5100	20.7	3170
0	32	4.579	6020	24.4	3640
2	36	5.294	6970	28.2	4330
4	39	6.101	8030	32.5	4990
6	43	7.013	9230	37.4	5730
8	46	8.045	10590	42.9	6580
10	50	9.209	12120	49.1	7530
12	54	10.52	13840	56.1	8600
14	57	11.99	15780	63.9	9800
16	61	13.63	17930	72.6	11140
18	64	15.48	20370	82.5	12650
20	68	17.54	23080	93.5	14330